

3-YEAR
WARRANTY

CONFORME
NORME
EN 131-4

**TELESCOPIC
LADDERS**



OPTI+ PRO // TELESCOPIC & MULTIPURPOSE



**UNLOCKING BY MERE
PRESSURE**

2 NON-SLIP PLATFORMS
Total surface 0,30 x 1,40 m.



✓ **ADJUSTABLE HEIGHT !**
Height adjustable rung by rung by
pulling the side handle.

Ultra safe and automatic locking
system in the different positions
of use.

**POSITION
WORKBENCH**



**ANODISED
ALUMINIUM**
KEEPS HANDS
CLEAN

Profiles in anodised aluminium to
keep hands clean (on the ladder's
articulated section)


Non-slip rungs 30 x 30 mm on
the articulated ladder.
Non-slip rungs 25 x 30 mm
on the telescopic ladder
section. Distance between
rungs 270 mm.

280 mm

Non-slip feet, bi-composite

**ULTRA-COMPACT WHEN
FOLDED**

Platforms easily store in
the middle of the folded
product.



5 POSSIBLE POSITIONS



SINGLE LADDER



WALL SPREADER



FREE STANDING



USE IN STAIRS

Video of the product's use available on
www.centaure.fr/rubric FAQ, or on

You Tube

| Item code | Barcode | Diagram 1 | Diagram 2 | Diagram 3 | Diagram 4 | Diagram 5 | Diagram 6 | Diagram 7 | Diagram 8 | Weight (kg) |
|--------------|---------------|-----------|------------|-----------|-----------|-----------------|-----------------|-----------------|-----------|-------------|
| 510853 | 3172965108538 | A et T | 72/63 (mm) | 2.45 (m) | 2.54 (m) | 0.62 - 0.90 (m) | 2.86 - 3.41 (m) | 1.37 - 1.64 (m) | | 16.70 |

A= articulated part 2 + 3 + 3 + 2. T= telescopic 3 + 3

SPARE PARTS

Stabilizer

380567

**Locking
button**

(sold by pairs)

380568