

## // WOODEN ROOF LADDERS



✓ **COMFORTABLE USE !**  
Rounded rungs (48 x 22 mm) striated and non-slip in resinous wood.  
Bevelled stiles at the top to ease the positioning of the ladder.



✓ **SUPER STRONG !**  
Stiles from Lamibois Kerto®  
Spruce wood entirely treated water repellent for more durability.

WOOD ROOF LADDER  
9 RUNGS

✓ **EFFICIENT ASSEMBLY !**  
4 screws fixed in diagonal  
to avoid the rotation of the rung.  
Easy replacement.

**MAXIMUM LOADING  
CAPACITY 150 KG.**

## OPTION

ALUMINIUM  
ROOF HOOK

## FOR EASY ACCESS TO ROOF






Optimal safety thanks to 2 super wide extended tubes.

## QUICK SET UP






Telescopic adjustment between the rungs with locking device.  
The hook is fixed on the 2 upper rungs of your wood roof ladder  
and is locked.  
2 wheels with rubber stripping and the large leaning surface  
prevent from damaging the roof.  
Adapts on the flat roof ladders.

Item code	Barcode	Diagram	(L x W x D) (m)	(kg)
480001	3 172965 102062		0.99 x 0.48 x 0.55	4.60

## Distance between rungs 25 cm

Item code					
	3 172965 102062		(m)	(L x W x D) (m)	(kg)
480111	3172964801119	11	3.00	3.00 x 0.38 x 0.05	6.30
480115	3172964801157	15	4.00	4.00 x 0.38 x 0.05	8.50
480119	3172964801195	19	5.00	5.00 x 0.38 x 0.05	10.70

## Distance between rungs 33 cm

Item code	 3 172965 102062		 (m)	 (L x W x D) (m)	 (kg)
482109	3172964821094	9	3.00	3.00 x 0.38 x 0.05	5.80
482112	3172964821124	12	4.00	4.00 x 0.38 x 0.05	7.80
482115	3172964821155	15	5.00	5.00 x 0.38 x 0.05	9.70



WOODEN ROOF LADDER

During jobs on roof ladders, one must use anti-fall protection equipments.