

5-YEAR WARRANTY



COMPLIANT WITH STANDARD EN 131



LADDERS FOR FIRE RESCUE & EMERGENCY SERVICES



SCS // SINGLE LADDERS

Reduced width (292 mm) to ease the grip, the handling and the storage.

Item code	Barcode	Diagram 1	Diagram 2	Diagram 3	Diagram 4	Weight
	3 172965 102062	(mm)	(m)	(m)	(L x W x D)	(kg)
418114	3172964181143	14	51	4.22	4.25 x 0.30 x 0.05	7.40



Upper part provided with aluminium hooks equipped with steel points at the ends

Non-slip aluminium rungs

SCS 14 RUNGS

280 mm

C2S // ROPE-OPERATED EXTENSION LADDERS 2 SECTIONS



The French Ministry of Interior recommends the use of the Centaure ladders.
17-18-0-214-M-19-03 / 18-0-214-M-19-03 et 18-010460-3



✓ **HIGH RESISTANCE!**
 Two-arm locking system in steel tested to resist 575 kg.

Oversized aluminium box profiles designed to stand the weight of 2 persons.

Ladder's feet equipped with wall skids to keep the ladder off the wall and leave room for the user's hands by climbing.



✓ **CONVENIENT!**
 Easy handling thanks to a mobile ring for the rope.

Item code	Barcode	Diagram 1	Diagram 2	Diagram 3	Diagram 4	Diagram 5	Weight
	3 172965 102062	(mm)	(m)	(m)	(m)	(L x W x D)	(kg)
418410	3172964184106	2x10	81	3.05	5.30	3.05 x 0.43 x 0.15	18.40
418416	3172964184168	2X16	100	4.75	8.10	4.75 x 0.43 x 0.21	27.90

SPARE PARTS
Articulated feet
 (sold by pairs)
 380151

Rope treated anti-UV.

Aluminium non-slip rungs



✓ **STABLE!**
 Large swivel feet equipped with a non-slip studded sole

C2S 2 X 10 RUNGS